

PC 60/115 T

Industrial Top Loading Automatic Parts Cleaner

An effective and efficient stainless steel, robust automatic top loading parts cleaner designed to clean, degrease, remove oil and preserve parts without the use of solvents. The cleaning liquid consists of 95-99% water with 1-5% alkaline Kärcher cleaning detergent and is applied via 3 dimensional stainless steel fan jet nozzles at a pressure of 1.5 bar. The operating temperature is thermostatically controlled in a range between 35-75 °C. Versatile in all areas of industrial and commercial parts cleaning such as in production, service, repair shops, car/commercial vehicle workshops, recycling and metalworking industries.

- Made entirely of stainless steel and therefore extremely robust
- Top loading machine with gas sprung cover
- 30 minute cleaning cycle timer
- Features a 3 dimensional fan jet nozzle system for thorough all round cleaning
- Stainless steel motorized rotary plate/table with containment ring
- Fully automatic oil skimmer and container
- Automatic water level monitor and dry run cut-out to protect heating system
- Debris & small parts strainer
- Mobile unit with lockable castors
- Ball valve and sloped bottom tank for easy emptying of waste liquid
- Connection for steam extraction
- Simple, easy to use control panel



TEL: 01295 752 082

Kärcher (UK) Ltd
Beaumont Road
Banbury
Oxon OX16 1TB
www.karcher.co.uk

Technical data		PC 60/115 T
Power supply	~V/Hz	3/420/50
Water flow rate	l/h	4550 l/h
Tank capacity	l	95
Operating pressure	bar	1,5
Working Temperature	°C	max. 90
Heater	kW	4,5
Load capacity	kg	115
Basket-Ø	mm	600
Loading height	mm	310
Weight	kg	192
Dimensions (L x W x H)	mm	990 x 1080 x 1230
Order number		1.626-700

Target Market

Car/Commercial vehicle-shops
 Service and garage companies
 Machine cleaning in industry
 Metalworking companies
 Recycling

Standard Accessories

- Containment ring for rotary plate (stainless steel)
- Small parts cage with cover (stainless steel)
- Operating hour meter
- Oil skimmer & container
- Automatic water level control & heating protection
- 30 minutes cleaning cycle timer

Optional Accessories

- Replacement filter cartridge (9.804-531)
- 2 channel 24h/7days timer for control of heating and oil skimmer (6.631-551)
- Detergents:
 - RM 38 Powder – (6.291-380)
Alkaline parts cleaner with corrosion inhibitor
 - RM 39 Liquid – (6.291-390)
Alkaline parts cleaner with corrosion inhibitor
 - RM 63 Powder – (6.291-630)
Alkaline intensive parts cleaner

